



KORTON INDUSTRIAL LIMITED



SKF FYRP 2.1/2-3 Flange Block Bearings

Bearing No. FYRP 2.1/2-3

FYRP 2.1/2-3 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	6.13
EAN	7316576664670
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	22213
Seals	Garter Spring
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch - Metric	Inch
Long Description	4 Bolt Round Flange Cartridge; 2-1/2" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Spherical Roller Bearing; 3-3/8" Length Thru B



KORTON INDUSTRIAL LIMITED

Other Features	Double Row Heavy Duty Open End With Set Screw
Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	FYRP 2.1/2-3
Weight / LBS	13.5
Nominal Bolt Circle Diameter Round	6.5 Inch 165 Millimeter
d	2.5 Inch 63.5 Millimeter
Cartridge Pilot Diameter	5.5 Inch 139.7 Millimeter
D	3.375 Inch 85.725 Millimeter
Bolt Spacing	4.6 Inch 117 Millimeter
Cartridge Pilot Depth	1 Inch 25.4 Millimeter
bore diameter:	2-1/2 in
expansion type:	Non-Expansion Bearing (Fixed)
bolt center-to-center length:	6.5000 in
seal type:	Radial Shaft Seal
overall length/diameter:	7.6250 in
overall depth:	3-1/2 in
flange mounting type:	Four-Bolt Piloted Flange
radial dynamic load capacity:	33300 lb
bearing type:	Spherical Roller
radial static load capacity:	41100 lb
housing construction:	Solid Flange Mount
operating temperature range:	-5 to +230 ° F
bore type:	Round



KORTON INDUSTRIAL LIMITED

maximum rpm:	1100 RPM
duty type:	Standard Duty
finish/coating:	Uncoated
housing material:	Cast Iron
lubrication type:	Lubrication Fitting
locking device:	Set Screw
series:	222